

# MIROR FLUORESCENT LOW-BAY

MN  
T5 & T8

- ◆ T5 lamps maintain over 95% of their original output
- ◆ For additional lighting control and energy savings - occupancy sensor is available
- ◆ Easy tool-less electrical access
- ◆ Electronic ballast standard
- ◆ All reflective surfaces constructed of enhanced specular anodized aluminum
- ◆ Housing constructed of heavy gauge die-formed cold rolled steel
- ◆ Available with Y-hanger and chain, Gripple Hang-Fast Suspension
- ◆ All parts painted after fabrication for safe handling and rust prevention
- ◆ UL listed for U.S. and Canada
- ◆ Optical Efficiency = > 94%


CRI = 85, High output lamps can be requested

High Frequency Electronic Ballast > 40 kHz

5 Year Ballast Warranty

High Power Factor > 98%

Ballast for 4FT lamps the total harmonic distortion < 20% at full light output



## ORDERING GUIDE

<b>MN</b>	<b>5</b>	-	<b>2L</b>	-	<b>OS</b>	-	<b>2B</b>	-	<b>UNV</b>
SERIES	TYPE		TOTAL LAMPS		OPTIONS		BALLAST TYPE		VOLTAGE

### SERIES

MN MIROR Narrow "Low Bay" Fixture

### TYPE

5 54 watt T5HO  
8 32 watt T8

### TOTAL LAMPS

(T5 ship w/ fixtures - 841K)  
(T8 ship w/ fixtures - 741K)

1L 1 lamp  
2L 2 lamps  
3L 3 lamps  
4L 4 lamps (2 lamp cross-section, 8' only)  
6L 6 lamps (3 lamp cross-section, 8' only)

### OPTIONS (ship with fixture)

OS Occupancy Sensor\*  
6C Cord, 6' length, black  
6C15TP 6' black cord, 15 amp, twistlock plug (voltage specific)  
6C20TP 6' black cord, 20 amp, twistlock plug (voltage specific)  
F54/850 Fluorescent lamp, 54 watt, 5000K  
F32/841 Fluorescent lamp, 32 watt, 4100K (CEE Approved)  
F32/850 Fluorescent lamp, 32 watt, 5000K  
E5 Emergency ballast, T5HO  
E8 Emergency ballast, T8

### ACCESSORIES (ship separately)

Y Y-hanger (1 pair)  
Y3 Y-hanger & 3' chain (1 pair)  
G10 Gripple Hang-Fast Suspension, 10' length (1 pair)

### BALLAST TYPE

1B (1) 1 lamp ballast  
2B (1) 2 lamp ballast  
3B (1) 3 lamp ballast  
4B (1) 4 lamp ballast  
22B (2) 2 lamp ballasts  
33B (2) 3 lamp ballasts  
42B (1) 4 lamp & (1) 2 lamp ballast

(CEE Approved Ballast Available)

### VOLTAGE

120 120V  
208 208V  
240 240V  
277 277V  
UNV 120 - 277V  
347\*\* 347V  
480\*\* 480V

\* Fixtures equipped with occupancy sensor must have a specified input voltage

\*\* Only available in 2 lamp ballasts

