



MIROR FLUORESCENT LOW-BAY

MN
T5 & T8

- ◆ T5 lamps maintain over 95% of their original output
 - ◆ For additional lighting control and energy savings - occupancy sensor is available
 - ◆ Easy tool-less electrical access
 - ◆ Electronic ballast standard
 - ◆ All reflective surfaces constructed of enhanced specular anodized aluminum
 - ◆ Housing constructed of heavy gauge die-formed cold rolled steel
 - ◆ Available with Y-hanger and chain, Gripple Hang-Fast Suspension
 - ◆ All parts painted after fabrication for safe handling and rust prevention
 - ◆ UL listed for U.S. and Canada
 - ◆ Optical Efficiency = > 94%
- CRI = 85, High output lamps can be requested
- High Frequency Electronic Ballast > 40 kHz
- 5 Year Ballast Warranty
- High Power Factor > 98%
- Ballast for 4FT lamps the total harmonic distortion < 20% at full light output



ORDERING GUIDE

MN	5	-	2L	-	OS	-	2B	-	UNV
SERIES	TYPE		TOTAL LAMPS		OPTIONS		BALLAST TYPE		VOLTAGE

SERIES

MN MIROR Narrow "Low Bay" Fixture

TYPE

5 54 watt T5HO
8 32 watt T8

TOTAL LAMPS

(T5 ship w/ fixtures - 841K)
(T8 ship w/ fixtures - 741K)

1L 1 lamp
2L 2 lamps
3L 3 lamps
4L 4 lamps (2 lamp cross-section, 8' only)
6L 6 lamps (3 lamp cross-section, 8' only)

OPTIONS (ship with fixture)

OS Occupancy Sensor*
6C Cord, 6' length, black
6C15TP 6' black cord, 15 amp, NEMA twistlock plug (voltage specific)
6C20TP 6' black cord, 15 amp, NEMA twistlock plug (voltage specific)
F54/850 Fluorescent lamp, 54 watt, 5000K
F32/841 Fluorescent lamp, 32 watt, 4100K (CEE Approved)
F32/850 Fluorescent lamp, 32 watt, 5000K
E5 Emergency ballast, T5HO
E8 Emergency ballast, T8

ACCESSORIES (ship separately)

Y Y-hanger (1 pair)
Y3 Y-hanger & 3' chain (1 pair)
G10 Gripple Hang-Fast Suspension, 10' length (1 pair)

BALLAST TYPE

1B (1) 1 lamp ballast
2B (1) 2 lamp ballast
3B (1) 3 lamp ballast
4B (1) 4 lamp ballast
22B (2) 2 lamp ballasts
33B (2) 3 lamp ballasts
42B (1) 4 lamp & (1) 2 lamp ballast

(CEE Approved Ballast Available)

VOLTAGE

120 120V
208 208V
240 240V
277 277V
UNV 120 - 277V
347** 347V
480** 480V

* Fixtures equipped with occupancy sensor must have a specified input voltage

** Only available in 2 lamp ballasts

