


# MIROR VAPORTIGHT HI-BAY

MWH  
T5 & T8


- ◆ Fiber Glass Reinforced Polyester Body
  - ◆ Polycarbonate or Clear Acrylic Lens
  - ◆ Closed Cell Polyurethane Gasket
  - ◆ 4 lamp T5 & 6 Lamp T8 up to 104°F, & 6 lamp T5 up to 77°F
  - ◆ NSF/ANSI Standard 2- Splash Zone
  - ◆ NEMA 4X - Indoor or Outdoor use
  - ◆ IP67 - Dust and Liquid Protected
  - ◆ RoHS Compliant
  - ◆ High Pressure Hose Down 1500 PSI
  - ◆ High Ambient and -20°F Cold start ballast options available
  - ◆ UL Listed for US & Canada
  - ◆ T8 lamps maintain over 90% of their original output and provide good color rendition
  - ◆ T5HO lamps maintain 95% of their original output and provide much better color rendition
  - ◆ Consumes 50% of the energy of a 400 watt metal halide and delivers comparable light levels, when replaced one-for-one
  - ◆ Just under 4" tall - allows placement near the ceiling for the optimal usage of space Electronic ballast standard
  - ◆ All reflective surfaces constructed of enhanced specular anodized aluminum
  - ◆ Housing constructed of heavy gauge die-formed cold rolled steel
- Optical Efficiency = 93%  
CRI = 85, High output lamps can be requested  
High Frequency Electronic Ballast > 40 kHz  
UL Listed & 5 Year Ballast Warranty  
High Power Factor > 98% Ballast for 4FT lamps  
the total harmonic distortion < 20% at full light output



Depth: 5.95"

## DIMENSIONS

Width 14.61" x Length 51.81" x Depth 5.95"



## ORDERING GUIDE

<b>MWH</b>	<b>5</b>	<b>-</b>	<b>6L</b>	<b>-</b>	<b>OS</b>	<b>-</b>	<b>42B</b>	<b>-</b>	<b>UNV</b>
SERIES	TYPE		TOTAL LAMPS		OPTIONS		BALLAST TYPE		VOLTAGE

### SERIES

MWH MIROR Vaportight Hi-Bay Fixture

### TYPE

5 54 watt T5HO  
8 32 watt T8

### TOTAL LAMPS (ship w/ fixtures - 841K)

4L 4 lamps  
6L 6 lamps

### OPTIONS (ship with fixture)

OS Occupancy Sensor\*  
6C Cord, 6' length, black  
6C15TP 6' black cord, 15 amp, twistlock plug (voltage specific)  
6C20TP 6' black cord, 20 amp, twistlock plug (voltage specific)  
HUB 3/4" cast iron hub and junction box  
HH Hub mount and hook  
F32/841 Fluorescent lamp, 32 watt, 4100K (CEE Approved)  
F32/850 Fluorescent lamp, 32 watt, 5000K  
F54/841 Fluorescent lamp, 54 watt, 4100K  
F54/850 Fluorescent lamp, 54 watt, 5000K  
E8 Emergency ballast, T8  
E5 Emergency ballast, T5  
CA Clear Acrylic Lens  
PC Polycarbonate Lens

### BALLAST TYPE

2B (1) 2 lamp ballast  
33B (2) 3 lamp ballasts  
42B (1) 4 lamp & (1) 2 lamp ballast  
222B (3) 2 lamp ballasts

(CEE Approved Ballast Available)

### VOLTAGE

120 120V  
208 208V  
240 240V  
277 277V  
UNV 120 - 277V  
347\*\* 347V  
480\*\*/\*\* 480V

### ACCESSORIES (ship separately)

Y Y-hanger (1 pair)  
Y3 Y-hanger & 3' chain (1 pair)  
G10 Gripple Hang-Fast Suspension, 10' length (1 pair)



\* Fixtures equipped with occupancy sensor must have a specified input voltage  
\*\* Only available in 2 lamp ballasts  
\*\*\* Ballast(s) are 277V input. T8 Fixture furnished with 480/277V step down transformer. Fixture accepts 480V supply voltage.